POWER RAKES

PR60 | PR72B | PR84B | PR96B

SPECIFICATIONS

- John Deere power rakes are perfect for landscape tasks such as seedbed preparation, rock raking, site development, and more.
- Adjustable end plates enable the power rake for double duty as a box scraper, trapping and gathering stones for piling and pickup.
- Long-life carbide teeth on the roller dig, lift, and pulverize dirt.
- Heavy-duty drive chain is housed in a sealed oil bath to reduce maintenance.
- Power rake roller assemblies can rotate 20 degrees from center in either direction, allowing material to be moved left or right (requires 12-volt kit).
- Forward and backward raking capability halves the time required for seedbed preparation.
- These power rakes are optimized to work with John Deere skid steer loaders (SSLs) and compact track loaders (CTLs). They're compatible with most competitive models.

	PR60	PR72B	PR84B	PR96B
Minimum Hydraulic Flow	49 L/min. (13 gpm)	49 L/min. (13 gpm)	60 L/min. (16 gpm)	60 L/min. (16 gpm)
Width				
Raking	1575 mm (62 in.)	1827 mm (72 in.)	2134 mm (84 in.)	2438 mm (90 in.)
Operating	1829 mm (72 in.)	2056 mm (81 in.)	2362 mm (93 in.)	2540 mm (100 in.)
Length	1499 mm (59 in.)	1625 mm (64 in.)	1625 mm (64 in.)	1930 mm (76 in.)
Height	787 mm (31 in.)	787 mm (31 in.)	812 mm (32 in.)	812 mm (32 in.)
Box End Plates	Front or rear	Front or rear	Front or rear	Front or rear
Tooth Roller Diameter	229 mm (9 in.)	229 mm (9 in.)	229 mm (9 in.)	229 mm (9 in.)
Weight	425 kg (938 lb.)	419 kg (925 lb.)	476 kg (1,050 lb.)	598 kg (1,320 lb.)
Angle Control (12-volt kit required)	12-volt actuation, 0–20-deg. rotation	12-volt actuation, 0–20-deg. rotation	12-volt actuation, 0–20-deg. rotation	12-volt actuation, 0–20-deg. rotation
Vehicle Compatibility	316GR and 318G SSLs	316GR, 318G, 320G, 324G, 330G, and 330 P-Tier SSLs; 317G and 325G CTLs	320G, 324G, 330G, and 330 P-Tier SSLs; 317G, 325G, 331G, 331 P-Tier, 333G, and 333 P-Tier CTLs	320G, 324G, 330G, and 330 P-Tier SSLs; 325G, 331G, 331 P-Tier, 333G, and 333 P-Tier CTLs