

ROTARY TILLERS

RT52 / RT66



SPECIFICATIONS

- RT52 and RT66 till up to a six-inch depth. Rugged construction and heavy-duty tines provide long service life and excellent operation in all conditions.
- Offset to the right six inches, both models are ideal for close tilling beside walls and sidewalks. The RT66 can also be positioned in the center.
- Tillers require only standard hydraulic flow for high-quality performance.
- For increased efficiency, till in both forward and reverse directions.
- Optional scarifiers increase productivity in hard ground conditions.
- These rotary tillers are optimized to work with John Deere skid steer loaders (SSLs) and compact track loaders (CTLs). They're also compatible with many competitive models.

	RT52	RT66
Tilling Width	1.3 m (52 in.)	1.7 m (66 in.)
Overall Width	1.6 m (62 in.)	1.9 m (76 in.)
Overall Length	122 cm (48 in.)	122 cm (48 in.)
Overall Height	89 cm (35 in.)	89 cm (35 in.)
Tilling Depth	15 cm (6 in.)	15 cm (6 in.)
Number of Tines	24	32
Number of Scarifiers (optional)	4	5
Hydraulic Flow		
Minimum	68 L/min. (18 gpm)	68 L/min. (18 gpm)
Maximum	106 L/min. (28 gpm)	106 L/min. (28 gpm)
Operating Weight		
Vehicle Compatibility	318G, 320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs	318G, 320G, 324G, 330G, and 332G SSLs; 325G, 331G, and 333G CTLs

[Learn more about Rotary Tillers](#)

[Back to Table of Contents](#)